



SPECS

TELAIO	
TAGLIE	XS, S, M, L, XL
COLORAZIONI	Rainbow Black
TELAIO	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
FORCELLA	RockShox Recon RL, 130mm travel, Lockout, 110x15mm MaxleLite
AMMORTIZZATORE	RockShox Monarch RT, High Volume, 184x44mm, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Connect TR Riser 31.8x780mm
ATTACCO MANUBRIO	Giant Contact
TUBOSELLA	Giant Contact Switch, dropper, 30,9mm (S:100/M:125/L:150/XL:170)
SELLA	Giant Contact, Neutral
PEDALI	-
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	SRAM SX Eagle 12-speed
DERAGLIATORE	-
CAMBIO	SRAM SX Eagle 12-speed
FRENI	Shimano MT420, 4-piston brakes, 203mm
COMANDI FRENO	Shimano MT401 Hydraulic Disc
PACCO PIGNONI	SRAM PG-1210, 11-50T, 12-Speed
CATENA	SRAM SX Eagle PowerLock, 12-speed
GUARNITURA	SRAM X-Sync Eagle 38T 104BCD chainring Forged Alloy minimal Q-factor, 38T Steel Direct Mount ring (XS/S:160, M/L:165, XL:170)
RUOTE	
DROP MOVIMENTO CENTRALE	N/A
CERCHI	Giant AM 27.5+, Tubeless ready, 35mm inner width
MOZZI	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR
RAGGI	Stainless Steel
COPERTURE	Maxxis Rekon 27.5x2.6", Exo protect, Tubeless Ready
EXTRA	Giant EnergyPak 6A Smart charger
TECNOLOGIA IBRIDA	
MOTORE	Giant SyncDrive Sport
SENSORI	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE
BATTERIA	Giant EnergyPak Smart 500, 36V 13.8Ah integrated Lithium-Ion

CARATTERISTICHE

- Telaio: ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
- Forcella: RockShox Recon RL, 130mm travel, Lockout, 110x15mm MaxleLite
- Leve del cambio: SRAM SX Eagle 12-speed
- Guarnitura: SRAM X-Sync Eagle 38T 104BCD chainring Forged Alloy minimal Q-factor, 38T Steel Direct Mount ring (XS/S:160, M/L:165, XL:170)
- Colorazioni: Rainbow Black

Prezzo: € 3.599,00

GEOMETRIA

TELAIO	XS	S	M	L	XL
Lunghezza tubo sella (mm)	380	406	432	482	507
Angolo tubo sella	73,5°	73,5°	73,5°	73,5°	73,5°
Lunghezza tubo orizzontale (mm)	565	580	600	625	650
Lunghezza tubo sterzo (mm)	100	100	110	120	135
Angolo sterzo	67,0°	67,0°	67,0°	67,0°	67,0°
Rake forcella (mm)	46	46	46	46	46
Trail (mm)	106,9	106,9	106,9	106,9	106,9
Interasse (mm)	1147	1162	1183	1209	1236
Lunghezza carro posteriore (mm)	465	465	465	465	465
Drop movimento centrale (mm)	20	20	20	20	20
Stack (mm)	590	590	599	608	622
Reach (mm)	390	405	422	444	465
Altezza stand over (mm)	715	731	746	778	781
Larghezza manubrio c/c (mm)	780	780	780	780	780
Lunghezza attacco manubrio (mm)	50	50	60	60	70
Larghezza pedivella (mm)	165	165	170	170	170
Dimensione ruote	27.5+	27.5+	27.5+	27.5+	27.5+

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Taglie disponibili per l'Italia da verificare con il B2B per ogni modello.