

# STANCE E+ 2 POWER



## SPECS

TELAIO	
TAGLIE	XS, S, M, L, XL
COLORAZIONI	Metallic Blue
TELAIO	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
FORCELLA	SR Suntour XCR 27.5+, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
AMMORTIZZATORE	RockShox Monarch R, 184x44mm, Standard Eyelet, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Connect TR, 31,8x780mm
ATTACCO MANUBRIO	Giant Connect
TUBOSELLA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLA	Giant Contact, Neutral
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	Shimano Deore
CAMBIO	Shimano SLX, 10-Speed, Shadow+
FRENI	Tektro HD-M735, 4/2-piston, hydraulic disc, 203mm
COMANDI FRENO	Tektro HD-M735
PACCO PIGNONI	Shimano HG50-10, 11-36T, 10-Speed
CATENA	KMC e.10 Sport, e-bike optimized
GUARNITURA	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring
RUOTE	
CERCHI	Giant AM 27.5+, Tubeless ready, 35mm inner width, e-bike optimized
MOZZI	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR, e-bike optimized
RAGGI	Stainless Steel
COPERTURE	Maxxis Rekon 27.5x2.6", Exo protect, Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart charger (60% charge in 60minutes)
TECNOLOGIA IBRIDA	
MOTORE	Giant SyncDrive Sport, 80Nm powered by YAMAHA, 350% tuneable support
SENSORS	Giant PedalPlus 4-sensor technology
DISPLAY	Giant RideControl ONE, remote button
BATTERIA	Giant EnergyPak 500, 36V 13.8Ah integrated Lithium-Ion

## CARATTERISTICHE

- Giant SyncDrive Sport motor, 80Nm powered by YAMAHA, 350% tuneable support
- Giant EnergyPak500 integrated lithium-ion battery
- SR Suntour XCR LO-R 130mm suspension fork
- Shimano Deore 1x10sp speed drivetrain
- Hydraulic disc brakes, 200mm rotors
- Color: Metallic Blue

Prezzo: € 3.199

## GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza tubo sella (mm)	406	432	482	507
Angolo tubo sella	73,5°	73,5°	73,5°	73,5°
Lunghezza tubo orizzontale (mm)	580	600	625	650
Lunghezza tubo sterzo (mm)	100	110	120	135
Angolo sterzo	67,0°	67,0°	67,0°	67,0°
Rake forcella (mm)	46	46	46	46
Trail (mm)	107	107	107	107
Interasse (mm)	1162	1183	1209	1236
Lunghezza carro posteriore (mm)	465	465	465	465
Drop movimento centrale (mm)	20	20	20	20
Stack (mm)	590	599	608	622
Reach (mm)	405	422	444	465
Altezza stand over (mm)	731	746	778	781
Larghezza manubrio c/c (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	50	60	60	70
Larghezza pedivella (mm)	165	170	170	170
Dimensione ruote	27.5+	27.5+	27.5+	27.5+

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso.