

# VALL E+ 3 POWER



## SPECS

TELAIO	
TAGLIE	XS, S, M, L
COLORAZIONI	Starry Gray / Metallic Purple
TELAIO	ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, 141mm Boost QR, integrated KS18 kickstand mount
FORCELLA	SR Suntour XCM34 Boost Coil NLO 27,5+ 120mm travel, Tapered 1½ - 1⅝" steerer, lockout
AMMORTIZZATORE	N/A
COMPONENTISTICA	
MANUBRIO	Giant Connect TR Riser
ATTACCO MANUBRIO	Giant Contact
TUBOSELLA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLA	Liv Sport
PEDALI	Aluminum Platform
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	Shimano SL-M2000
DERAGLIATORE	-
CAMBIO	Shimano Deore, 9-Speed, Shadow design
FRENI	Tektro HD-M286, hydraulic disc, 180mm
COMANDI FRENO	Tektro HD-M285
PACCO PIGNONI	Shimano CS-HG200, 11-36T, 9-Speed
CATENA	KMC e.9 Sport, e-bike optimized
GUARNITURA	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring
RUOTE	
DROP MOVIMENTO CENTRALE	N/A
CERCHI	Giant AM 27.5, Tubeless ready, 30mm inner width, e-bike optimized
MOZZI	Giant eTracker Boost, [F] 15mm Thru-Axle [R] 148x12mm Thru-axle, e-bike optimized
RAGGI	Stainless steel
COPERTURE	Maxxis Forekaster 27.5x2.6, foldable, 60 TPI, EXO, Tubeless ready
EXTRA	Giant EnergyPak 4A fast charger
TECNOLOGIA IBRIDA	
MOTORE	Giant SyncDrive Sport, 70Nm, 350% tuneable support with automatic smart support
SENSORI	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE, remote button
BATTERIA	Giant EnergyPak500, 36V 13.8Ah Rechargeable Lithium-Ion

## CARATTERISTICHE

- Telaio: ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, 141mm Boost QR, integrated KS18 kickstand mount
- Forcella: SR Suntour XCM34 Boost Coil NLO 27,5+ 120mm travel, Tapered 1½ - 1⅝" steerer, lockout
- Leve del cambio: Shimano SL-M2000
- Guarnitura: Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring
- Colorazioni: Starry Gray / Metallic Purple

Prezzo: € 2.299,00

## GEOMETRIA

TELAIO	XS	S	M	L
Lunghezza tubo sella (mm)	365	405	460	510
Angolo tubo sella	74,0°	73,5°	73,0°	73,0°
Lunghezza tubo orizzontale (mm)	550	565	585	600
Lunghezza tubo sterzo (mm)	110	115	135	150
Angolo sterzo	68,0°	68,0°	68,0°	68,0°
Rake forcella (mm)	42	42	42	42
Trail (mm)	100,2	100,2	100,2	100,2
Interasse (mm)	1116	1126	1142	1158
Lunghezza carro posteriore (mm)	475	475	475	475
Drop movimento centrale (mm)	50	50	50	50
Stack (mm)	612	617	635	649
Reach (mm)	374	382	390	401
Altezza stand over (mm)	674	696	742	763
Larghezza manubrio c/c (mm)	690	690	750	750
Lunghezza attacco manubrio (mm)	50	50	60	70
Larghezza pedivella (mm)	170	170	170	170
Dimensione ruote	27.5+	27.5+	27.5+	27.5+

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Taglie disponibili per l'Italia da verificare con il B2B per ogni modello.